

# Interface® | Straightforward

## TECHNISCHE SPECIFICATIES

<b>Type</b>	Microtuft bouclé	<b>Style Number</b>	<b>3081230005</b>
<b>Poolmateriaal</b>	100% Solution Dyed Polyamide BCF, bevat pre-consumer gerecycled content	<b>Gebruiksintensiteit</b>	EN 1307 33 Heavy Contract
<b>Poolinzetgewicht</b>	400g/m <sup>2</sup> ± 5%	<b>Radiant panel</b>	(EN ISO 9239/1) Cfl S1 (EN ISO 13501)
<b>Totaalgewicht</b>	4179g/m <sup>2</sup> ± 5%	<b>Hot Metal Nut</b>	Pass, low radius of effects of ignition (BS 4790)
<b>Poolhoogte</b>		<b>Rolstoelgeschikt</b>	≥ 2.4 (EN 985)
<b>Totale dikte</b>	4.8 mm ± 0.5 mm	<b>Dimensionele stabiliteit</b>	≤ 0.2% (ISO 2551 / EN 986)
<b>Rijen per 10 cm</b>	5/64 - 50.4	<b>Doorlaatweerstand</b>	5 x 10 <sup>5</sup> Ω >> 1 x 10 <sup>9</sup> Ω Computerguard (ISO 10965) (IBM)
<b>Aantal noppen per m2</b>	176,400 ± 5%	<b>Kleurechtheden - Licht</b>	7 (ISO 105/B02)
<b>Ruguitvoering</b>	Graphlex®	<b>Aantal tegels per doos</b>	20 - 5m <sup>2</sup> (50 x 50 cm ± 0.15%)

CE  
06  
0336-CPD-8538  
Cfl-s1  
BS  
EN 1307

www.interface.com

Non-Directional  
Gut  
EMS 32802  
OBBC9DAE 15dB  
EM 00679  
red:dot design award winner 2008  
material award  
ISO 14001  
Environmental Profile Scheme Certificate Number ENP-005



**Mission Zero:**  
our promise to eliminate  
any negative impact our company  
may have on the environment  
by the year 2020.

Technische wijzigingen, ter verbetering van het product, worden voorbehouden